FORM PTO-13	U.S. DEPARTMENT OF COMMERCE PATENT AND TRADEMARK OFFICE	ATTORNEY'S DOCKET NUMBER
(REV 5-95) TR	ANSMITTAL LETTER TO THE UNITED STATES	R0108T
	ESIGNATED/ELECTED OFFICE (DO/EO/US)	U.S. APPLICATION NO. (If known, see)7 CFR 1 5)
	ONCERNING A FILING UNDER 35 U.S.C. 371	^{N/} 09/980623
i	TONAL APPLICATION NO. INTERNATIONAL FILING DATE	PRIORITY DATE CLAIMED
	/JP00/01935 March 29, 2000	July 19, 1999
HEA	T EXCHANGER	
	TT(S) FOR DO/EO/US eo SAKURADA and Soichi KATO	
Applicant l	erewith submits to the United States Designated/Elected Office (DO/EO/US) the follower	owing items and other information:
2. 1 3. 1	his is a FIRST submission of items concerning a filing under 35 U.S.C. 371. his is a SECOND or SUBSEQUENT submission of items concerning a filing under his express request to begin national examination procedures (35 U.S.C. 371(f)) at an examination until the expiration of the applicable time limit set in 35 U.S.C. 371(b) an approper Demand for International Preliminary Examination was made by the 19th mo	y time rather than delay d PCT Articles 22 and 39(1).
a L	copy of the International Application as filed (35 U.S.C. 371(c)(2)) is transmitted herewith (required only if not transmitted by the International Bureau. is not required, as the application was filed in the United States Receintranslation of the International Application into English (35 U.S.C. 371(c)(2))	ving Office (RO/US)
a t	mendments to the claims of the International Application under PCT Article are transmitted herewith (required only if not transmitted by the International Bureau. have been transmitted by the International Bureau. have not been made; however, the time limit for making such amendr have not been made and will not be made.	national Bureau).
	translation of the amendments to the claims under PCT Article 19 (35 U.S.	C. 371(c)(3)).
	n oath or declaration of the inventor(s) (35 U.S.C. 371(c)(4)).	
10. 🗆 🗸	translation of the annexes to the International Preliminary Examination Rep. 35 U.S.C. 371(c)(5)).	ort under PCT Article 36
	to 16. below concern other document(s) or information included: in Information Disclosure Statement under 37 CFR 1.97 and 1.98.	
12. V	n assignment document for recording. A separate cover sheet in compliance	with 37 CFR 3.28 and 3.31 is included.
	FIRST preliminary amendment. SECOND or SUBSEQUENT preliminary amendment.	
14. 🗆 🗸	substitute specification.	
15. 🗆 /	change of power of attorney and/or address letter.	1
16. 🗆 (other items or information:	

NA9/98062	1 4	PCT/JP00/01935			ATTORNEYS DOO	XET YUMBER
17. The following fees as				CH	R0108T	PTO LSE JALL
Basic National Fee		(1) (5))•		CAL	CULATIONS	PIO CSE JACE
Search Report has bee	n prepared by th	e EPO or JPOS	830.00			
International preliminar	y examination fee	paid to USPTO (37 CFR 1.48				•
No international prelim	inary examination	fee paid to USPTO (37 CFR	640.00 1.482)	İ		
but international search	fee paid to USPI	CO (37 CFR 1.445(a)(2)) S	710.00			
		ation fee (37 CFR 1.482) nor (2)) paid to USPTO \$	950.00			
International preliminar and all claims satisfied	y examination fee provisions of PC	paid to USPTO (37 CFR 1.48 T Article 33(2)-(4)	32) \$ 90.00			· · · · · · · · · · · · · · · · · · ·
		ATE BASIC FEE AMO	UNT =	\$	290	
Surcharge of \$130.00 for furnimenths from the earliest claim			30	\$		
	ber Filed	Number Extra	Rate			
Total Claims	[B -20 =	0	X \$22.00	\$	0	
Independent Claims	j -3 =	0	X \$74.00	\$	O	
Multiple dependent claims(s) (+ \$230.00		0	
		ABOVE CALCULATION		\$	D	
Reduction by 1/2 for filing by must also be filed. (Note 3	small entity, if and 7 CFR 1.9, 1.27,	pplicable. Verified Small Ent 1.28).	tity statement	\$		-
	·	SUBTO	TAL =	\$		
Processing fee of \$130.00 for	furnishing the En		20 30	-		
months from the earliest clair		(37 CFR 1.492(f)).	+	\$		
		TOTAL NATIONAL		\$	890	
accompanied by an appropria		CFR 1.21(h)). The assignment (CFR 3.28 3.31). \$40.00 per		\$	40	
nei appropria	ac cover sheet (57	TOTAL FEES ENCLO	property '		930	
P-22				<u> </u>	mount to be:	
					refunded	\$
					charged	
a. A check in the amoun	t of \$ 930	to cover the above fees is e	nclosed.			
b. Please charge my Dep A duplicate copy of th			nt of \$		to cover	the above fees.
The Commissioner is	h analas assels 1					
overpayment to Depos	sit Account No	to charge any additional fees <u>ಎ0 - 00 んり</u> . A duplic	which may be ate copy of the	requir	red, or credit a et is enclosed.	ny
NOTE: Where an appropris	te time limit und	ler 37 CFD 1 404 or 1 405 be	a nat baan m		atitian ta ward	un (37 CED
1.137(a) or (b)) must be filed	and granted to	restore the application to pen	ding status.	er, a p	etition to revi	ve (3/ CFR
			•	W	7	f.
SEND ALL CORRESPONDENCE	m.		_	1	3. Take	mm
KANESAKA & TA			SIGNATU			1
1423 Powhatan	Street			Y	usuke Ta	Keuchi
Alexandria, V			NAME	3	0,921	
	Attn: Yusuke Takeuchi Tel: (703)519-9785					
			REGISTRA	TION NU	JMBER.	
Fax; (703)519	-7769	•				

IN THE UNITED STATED PATENT AND TRADEMARK OFFICE

Applicant: SAKURADA, M Group Art Unit: N/A

Serial No. N/A

Examiner: N/A

Filed: 12/06/01

Title: HEAT EXCHANGER

PRELIMINARY AMENDMENT

Assistant Commissioner of Patents Submitted: 12/06/01 Washington, D.C. 20231

Dear Sir:

Please amend the above-identified patent application as follows:

In the Claim:

Please amend claims 4-6 to read as follows:

- --4. (Amended) The heat exchanger according to claim 1 or 2, wherein the two or more heat exchangers disposed in parallel have a space of 15 mm or less between them.
- 5. (Amended) The heat exchanger according to claim 1 or 2, wherein one of the heat exchangers is a condenser and the other is a radiator.
- (Amended) The heat exchanger according to claim 1 or 2, wherein the two or more heat exchangers are integrally configured using a common member .--

REMARKS

Application Number: N/A

Art Unit: N/A

page 2

This amendment is to avoid multiple depending claims which are dependent upon another multiple depending claim.

Respectfully submitted,

Yusuke Takeuchi

Reg. No. 30,921

Agent for Applicant,

Date: 12/05/0/

KANESAKA & TAKEUCHI

1423 Powhaten Street

Alexandria, VA 22314

Tel.: (703)519-9785

Application Number: N/A page 3

Art Unit: N/A

VERSION WITH MARKINGS TO SHOW CHANGES MADE

- --4. (Amended) The heat exchanger according to [any of claims 1 to 3] <u>claim 1 or 2</u>, wherein the two or more heat exchangers disposed in parallel have a space of 15 mm or less between them.
- 5. (Amended) The heat exchanger according to [any of claims 1 to 4] claim 1 or 2, wherein one of the heat exchangers is a condenser and the other is a radiator.
- 6. (Amended) The heat exchanger according to [any of claims 1 to 5] claim 1 or 2, wherein the two or more heat exchangers are integrally configured using a common member.--

4/py/>>
HEAT EXCHANGER

TECHNICAL FIELD

The present invention relates to a heat exchanger which is comprised of two or more heat exchangers having different usage.

BACKGROUND ART

Conventional heat exchangers used for vehicles include for example a heat exchanger which is comprised of two or more heat exchangers having different operations.

For example, Japanese Patent Application Laid-Open Publication No. Hei 10-306994 discloses an invention of a heat exchanger which has a radiator core section for an engine and a condenser core section for a vehicle air conditioner configured integrally. And, Japanese Patent Application Laid-Open Publication No. Hei 10-253276 has paid attention to a ratio between a width of fins and a number of louvers, which are disposed between tubes of a condenser core section and a radiator core section, and configures so that a heat exchanger having a small required radiation amount between two integrally configured heat exchangers has a small ratio between the fin width and the number of louvers and a heat exchanger having a large required radiation amount has a ratio between the fin width and the number of louvers larger than that of the heat exchanger having the above small required radiation amount.

And, Japanese Patent Application Laid-Open Publication No. Hei 10-170184 has paid attention to the shape of louvers

formed on fins disposed between tubes of two heat exchangers, and improved the heat exchange efficiency of the two heat exchangers by configuring so that the louvers formed on the fins which are fitted to one of the heat exchangers have a shape different from louvers formed on the fins which are fitted to the other heat exchanger.

When two or more heat exchangers are disposed in parallel to a ventilating direction as in the invention described in the above publication, e.g., when the two or more heat exchangers are mounted on a vehicle, a flow of outside air is disturbed by the heat exchanger positioned on the windward side with respect to the ventilating direction. Thus, it is difficult to keep the heat-exchanging performance of the heat exchanger positioned on the leeward side.

Specifically, as shown in Fig. 4, when height h'c of tubes 13 configuring a first heat exchanger and height h'r of tubes 14 configuring a second heat exchanger are identical, a speed of air which has passed through the tubes 13 of the first heat exchanger is lowered by the presence of the tubes 13 of the first heat exchanger disposed on the windward of the ventilating direction and then the air is spread, so that the air speed is lowered along the surfaces of the tubes 14 and the portions of fins 6 in proximity to the tubes of the second heat exchanger, and the heat-exchanging performance of the second heat exchanger is significantly lowered.

To mount the heat exchangers within an engine room having a limited mounting space, the first and second heat exchangers must be mutually placed as close as possible, and they are also

demanded to be light-weighted.

Especially, when the tubes are disposed at right angles to the ventilating direction, outside air does not come into contact with the surfaces of the tubes of the second heat exchanger through which a high-temperature medium flows, so that the heat-exchanging performance is disturbed. Specially, when the tubes configuring the first and second heat exchangers have the same pitch, outside air does not flow along the surfaces of the tubes configuring the second heat exchanger, and a heat radiation amount of the second heat exchanger is lowered considerably.

Accordingly, the present invention has been completed in view of the aforesaid disadvantages, and it is an object of the invention to provide a heat exchanger which is comprised of two or more heat exchangers disposed in parallel at right angles to a ventilating direction and which can keep the heat-exchanging performance of a heat exchanger disposed on the leeward side.

SUMMARY OF THE INVENTION

The invention described in claim 1 of this application is a heat exchanger comprised of two or more heat exchangers which are disposed on the windward and leeward side of a ventilating direction in parallel at right angles to the ventilating direction, wherein the heat exchangers are configured by stacking a plurality of tubes; and the heights of the tubes of one heat exchanger disposed on the windward of the ventilating direction are lower than the heights of the

tubes of the other heat exchanger disposed on the leeward side.

Thus, when the two or more heat exchangers are disposed in parallel at right angles to the ventilating direction and the heights of the tubes of the heat exchanger on the windward are smaller than the heights of the tubes of the heat exchanger disposed on the leeward side, outside air which is to flow between the tubes and the fins of the heat exchangers flows along the surfaces of tubes of the heat exchanger disposed on the leeward side without being disturbed by the tubes of the heat exchanger disposed on the windward. Thus, heat is radiated from the tubes through which a high-temperature medium flows, and the heat-exchanging performance of the second heat exchanger disposed on the leeward side can be kept.

The invention described in claim 2 of the application is directed to the invention according to claim 1, wherein the respective tubes of the two or more heat exchangers disposed in parallel have approximately the same space between the stacked tubes.

For example, when the first heat exchanger and the second heat exchanger are disposed in parallel at right angles to the ventilating direction, especially when the stacked tubes configuring the first heat exchanger and the second heat exchanger have the same space between them and the same height or the heights of the tubes of the first heat exchanger is higher, the speed of the outside air having passed through the tubes of the first heat exchanger is lowered by the presence of the tubes of the first heat exchanger which is on the windward in the ventilating direction. And, the outside air having passed

through the first heat exchanger is spread and its speed is lowered on the surfaces of the tubes and the portions of the fins in proximity to the tubes of the second heat exchanger, and the heat-exchanging performance of the second heat exchanger is lowered considerably.

In this embodiment, even when the stacked tubes configuring the first and second heat exchangers have substantially the same space, the heights of the tubes configuring the first heat exchanger are lower than the heights of the tubes configuring the second heat exchanger, so that ventilation of the outside air is not disturbed, and the outside air is allowed to reach the surfaces of the tubes configuring the second heat exchanger. Thus, the heat-exchanging performance of the second heat exchanger can be kept.

The invention described in claim 3 is directed to the invention according to claim 1 or 2, wherein the respective tubes have a height of less than 1.6 mm.

The tubes configuring the heat exchanger are desired to have a height of 1.6 mm or less in view of the heat-exchanging efficiency of the heat exchanger and its weight reduction. Especially, when the first heat exchanger is a condenser, the heat-exchanging efficiency is further improved by determining the tubes to have a height of 1.3 mm or less, and it becomes possible to make the heat exchanger more compact and light-weighted.

The invention described in claim 4 is directed to the invention according to any of claims 1 to 3, wherein the two or more heat exchangers disposed in parallel have a space of

15 mm or less between them.

For example, when the first and second heat exchangers are mounted in an engine room, it is desired to mount the first and second heat exchangers, which are disposed in parallel, as close as possible to each other in order to reduce a mounting space. Meanwhile, when the first and second heat exchangers are disposed adjacent to each other, the outside air flowing to the second heat exchanger is disturbed by the first heat exchanger disposed on the windward in the ventilating direction, and the heat-exchanging performance of the heat exchanger disposed on the leeward side in the ventilating direction cannot be kept.

It is determined by the present invention that the heights of the tubes configuring the heat exchanger disposed on the windward are smaller than the heights of the tubes configuring the heat exchanger disposed on the leeward side. Therefore, the heat-exchanging performance of the second heat exchanger can be kept even if the first and second heat exchangers are disposed closely to have a space of 15 mm between them.

The invention described in claim 5 is directed to the invention according to any of claims 1 to 4, wherein one of the heat exchangers is a condenser and the other is a radiator.

In other words, the heat exchangers to be mounted closely to each other in the engine room are often comprised of the condenser configuring a heat exchange cycle for air conditioning and the radiator for cooling an engine, which are required to have high heat-exchanging performance.

The invention described in claim 6 is directed to the

invention according to any of claims 1 to 5, wherein the two or more heat exchangers are integrally configured using a common member.

When the two or more heat exchangers are integrally configured by a common member, for example, a bracket, the heat exchangers are light-weighted, and their mounting in the engine room or the like is facilitated without increasing the mounting space.

BRIEF DESCRIPTION OF THE DRAWINGS

Fig. 1 is a perspective view schematically showing the structure of first and second heat exchangers according to an embodiment of the present invention;

Fig. 2 is a partially sectional view of the heat exchangers of Fig. 1 according to the embodiment of the invention;

Fig. 3 is a diagram showing a relation between a ratio of the heights of tubes configuring the first and second heat exchangers and a ratio of a heat radiation amount of the second heat exchanger according to the embodiment of the invention; and

Fig. 4 is a partially sectional view of first and second heat exchangers according to prior art.

BEST MODE FOR CARRYING OUT THE INVENTION

Fig. 1 is a perspective view schematically showing the structure of this embodiment.

As shown in Fig. 1, the heat exchanger of this embodiment

has first and second heat exchangers 1, 2 which are disposed in parallel with respect to a ventilating direction.

The individual heat exchangers 1, 2 have a plurality of tubes 3, 4 and fins 5, 6 fitted between the tubes 3, 4 to increase a radiation area. The tubes 3, 4 and the fins 5, 6 are stacked into a plurality of layers, and each end of the tubes 3, 4 is connected to header tanks 7, 8, 9, 10. A heat-exchanging medium is distributed to flow from the respective header tanks 7, 8 to the individual tubes 3, 4 to perform heat exchange so that the high-temperature medium becomes a low-temperature medium by radiation from the tubes 3, 4 and the fins 5, 6.

An arrow in Fig. 1 indicates a ventilating direction of outside air.

The first and second heat exchangers 1, 2 of this embodiment are supported and integrally configured by common members. In this embodiment, brackets 15 are used to fix the first and second heat exchangers 1, 2 with bolts. Specifically, two brackets 15 each are disposed on the top and bottom of end plates of both heat exchangers, and a bolt is inserted for fixing through each bracket in the longitudinal direction of a vehicle. Thus, when the first and second heat exchangers are integrally configured by the common members, the brackets which have been separately fitted to the respective heat exchangers can be eliminated by virtue of the common member. Thus, the heat exchangers can be light-weighted and mounted in an engine room with ease.

In this embodiment, a condenser for a vehicle air conditioner which is the first heat exchanger 1 is disposed on

the windward of the ventilating direction, and an engine radiator which is the second heat exchanger 2 is disposed on the leeward side of the ventilating direction.

The heat exchangers 1, 2 of this embodiment have a space K of 15 mm between the condenser as the first heat exchanger 1 and the radiator as the second heat exchanger 2 in order to reduce a mounting space. Especially, it is significant to reduce the mounting space in order to mount the heat exchangers on a vehicle.

Thus, when the first heat exchanger 1 and the second heat exchanger 2 are closely mounted to each other, ventilation of outside air is disturbed by the first heat exchanger 1 which is disposed on the windward of the ventilating direction, and the outside air does not flow through the second heat exchanger 2, particularly along the surfaces of the tubes 4 through which the medium flows. Thus, a desired heat-exchanging performance cannot be obtained.

Therefore, in this embodiment, height hc of the tubes configuring the first heat exchanger 1 which is disposed in parallel to the second heat exchanger and at right angles to the ventilating direction is determined to be smaller than height hr of the tubes configuring the second heat exchanger 2.

In other words, the heights of the tubes configuring the first and second heat exchangers which are disposed in parallel at right angles to the ventilating direction have a relation of hc < hr.

Fig. 2 is a partially sectional view of the first and

second heat exchangers 1, 2, showing the tubes 3, 4 and the fins 5, 6. In Fig. 2, reference numerals 11, 12 indicate louvers formed on the fins 5, 6. The arrows in the drawing indicate the ventilating direction of outside air.

Fig. 3 is a diagram showing a relation between a ratio of the heights of the tubes configuring the first and second heat exchangers and a heat radiation amount of the second heat exchanger.

As shown in Fig. 3, the ratio of the heat radiation amount of the second heat exchanger is improved when hr/hc > 1 or more, namely when the heights of the tubes of the condenser disposed on the windward of the ventilating direction are smaller than the heights of the tubes of the radiator disposed on the leeward side of the ventilating direction.

In Fig. 3, a point B indicates that a relation between the height h'c of the tubes of the first heat exchanger and the height h'r of the tubes of the second heat exchanger is h'c = h'r.

A Point A in Fig. 3 indicates that a relation between the heights of the tubes 3, 4 of the first and second heat exchangers is hr/hc > 1 shown in this embodiment.

A Point C in Fig. 3 indicates that a relation between the heights hr and hc of the tubes of the first and second heat exchangers is hr/hc < 1.

The tubes 3, 4 configuring the heat exchangers 1, 2 are desired to have a height of less than 1.6 mm considering the heat-exchanging performance and weight reduction of the heat exchangers. Particularly, when the first heat exchanger is a

condenser as in this embodiment, the heat-exchanging efficiency is improved furthermore by determining the tubes to have a height of 1.3 mm or less. And, the heat exchanger can be made more compact and light-weighted.

Accordingly, the tubes 3, 4 of the heat exchangers 1, 2 are formed in this embodiment basically to satisfy the relation of hc < hr < 1.6 mm.

By forming the first and second heat exchangers using the tubes meeting the above inequality, the heat-exchanging performance of the second heat exchanger can be improved better than before without increasing the mounting space.

The condenser used for a heat-exchanging cycle of a car air conditioner and the radiator for cooling an engine are disposed in an engine room in parallel at right angles to the ventilating direction.

When the tubes of the condenser as the first heat exchanger are configured to have a height smaller than the heights of the tubes of the radiator as the second heat exchanger as in this embodiment, the heat-exchanging performance of the second heat exchanger is not disturbed by the first heat exchanger, and the required high heat-exchanging performance can be obtained.

INDUSTRIAL APPLICABILITY

The heat exchanger according to the present invention, which is comprised of two or more heat exchangers disposed in parallel on the windward and leeward in the ventilating direction, can improve the heat-exchanging performance of the

second heat exchanger disposed on the leeward side, so that the heat exchanger can be made compact and light-weighted.

Especially, the heat exchanger of the invention is suitable for a refrigerating cycle for vehicles and household appliances.

CLAIMS:


1. A heat exchanger comprised of two or more heat exchangers which are disposed on the windward and leeward side of a ventilating direction in parallel at right angles to the ventilating direction, wherein:

the heat exchangers are configured by stacking a plurality of tubes; and

the heights of the tubes of one heat exchanger disposed on the windward of the ventilating direction are lower than the heights of the tubes of the other heat exchanger disposed on the leeward side.

- 2. The heat exchanger according to claim 1, wherein the respective tubes of the two or more heat exchangers disposed in parallel have substantially the same space between the stacked tubes.
- 3. The heat exchanger according to claim 1 or 2, wherein the respective tubes have a height of less than 1.6 mm.
- 4. The heat exchanger according to any of claims 1 to 3, wherein the two or more heat exchangers disposed in parallel have a space of 15 mm or less between them.

- 5. The heat exchanger according to any of claims 1 to 4, wherein one of the heat exchangers is a condenser and the other is a radiator.
- 6. The heat exchanger according to any of claims 1 to 5, wherein the two or more heat exchangers are integrally configured using a common member.








FIG.3





Ratio of tube heights(hr/hc)




FIG.4

4

I hereby claim the benefit under Title 35, United States Code, §120 of any United States application(s) or PCT international application(s) designating the United States of America that is/are listed below and, insofar as the subject matter of each of the claims of this application is not disclosed in that/those prior application(s) in the manner provided by the first paragraph of Title 35, United States Code, §112, I acknowlege the duty to disclose material information as defined in Title 37, Code of Federal Regulations, §1.56(a) which occurred between the

	PRIO: 35 U.	R U.S. APPLICATION S.C. 120:	NS OR PCT II	NTERNAT	IONAL AP	PLICATIONS D	ESIGNATING	THE U.S. F	OR BENEFIT	UNDER	
	U.S. APPLICATIONS							STATUS (Check one)			
	U.S. APPLICATION NUMBER			U.S FILING DATE			PATENTED	PENDING	ABANOONE		
L											
_											
	·										
	·	PCT APPL	CATIONS DES	IGNATING	THE U.S.						
ati.	PCT APPLICATION NO PCT FILE			NG DATE U.S. SERIAL NUMBERS ASSIGNED (if any)							
- -			······································							ļ	
1										 	
Marie Commence	this a	ER OF ATTORNEY: oplication and transa umber) Yusu Mana	ct all busines	s in the P	atent and	Trademark Office 10. 30,921	e connected	therewith. (I	List name and	registra-	
Send Correspondence to: Yusuke Takeuchi KANESAKA & TAKEU 727 S. 23rd Stre Arlington, VA 22			CAKEUC Stree	eet			Direct Telephone Calls to: [name and telephone number] Yusuke Takeuchi (703) 521-3810				
	FULL NAME OF INVENTOR	FAMILY NAME Sakur	ada [_	er [IRST GIVEN NA	Muneo		SECOND GIVE	NAME		
201	RESIDENCE & CITIZENSHIP	cıry Saita	ıma	PYS	TATE OR FORE	ign country Japan		COUNTRY OF (otizenship pan		
	POST OFFICE ADDRESS	c/o Zexcel Veleo C 39, Aza-Higashihar				ato-gun Saitama	·	STATE & ZIP C	ODE/COUNTRY 0-0193	Japan	
	FULL NAME OF INVENTOR	FAMILY NAME	2 1		IRST GIVEN NA	ME	·····	SECOND GIVEN		Japan	
202	RESIDENCE &	(Kato	-0-0	\ / 	TATE OR FORE	Soichi IGN COUNTRY		COUNTRY OF	CITIZENSHIP		
×	POST OFFICE	Saitama \			Japan gation			Japan STATE & ZIP CODE/COUNTRY			
	ADDRESS	39, Aza-Higashihara		, Kohnan-n	machi, Oosa			36	0-0193	Japan	
	FULL NAME OF INVENTOR	FAMILY NAME		FI	RST GIVEN NA	ME		SECOND GIVEN	NAME		
203	RESIDENCE & CITIZENSHIP	CITY			STATE OR FOREIGN COUNTRY		COUNTRY OF CITIZENSHIP				
	POST OFFICE ADDRESS	POST OFFICE ADDRESS			CITY		STATE & ZIP CODE/COUNTRY				
SIGA	inform that w 1001 c	by declare that all ation and belief ar illful false statement of Title 18 of the Uplication or any pate	e believed to nts and the l Inited States ent issuing th	be true; ike so ma Code, ar tereon.	and furtlade are pu	ner that these : inishable by fir	statements ne or impris statements	were made vonment, or	with the know both, under s dize the valid	wledge section	
	·)	CIII		0 -	0.	1 / 1	1				
DAT	nuneo	-Sakurado		Sou	M	Kato. 2001					

COMBINED DECLARATION FOR PATENT APPLICATION AND POWER OF ATTORNEY (Inchides Reference to PCT International Applications)

As a below named inventor, I hereby declare that:

1999

i sila

My residence, post office address and citizenship are as stated below next to my name.

I believe I am the original, first and sole inventor (if only one name is listed below) or an original, first and joint inventor (if plural names are listed below) of the subject matter which is claimed and for which a patent is sought on the invention entitled:

ON THE INVENTION ENTITIES: HEAT EXCHANGER	
MANT ENGLIANGER	
the specification of which (check only one item below):	
Is attached hereto.	
was filed as United States application	
Scrial No.	
on	
and was amended	
on	(if applicable).
was filed as PCT international application	
Number PCT/JP00/01935	
on March 29,2000	A.
and was amended under PCT Article 19	
on	(if applicable).

I hereby state that I have reviewed and understand the contents of the above-identified specification, including the claims, as amended by any amendment referred to above.

I acknowlege the duty to disclose information which is material to the examination of this application in accordance with Title 37. Code of Federal Regulations, §1.56(a).

I hereby claim foreign priority benefits under Title 35, United States Code, §119 of any foreign application(s) for patent or inventor's certificate or of any PCT international application(s) designating at least one country other than the United States of America listed below and have also identified below any foreign application(s) for patent or inventor's certificate or any PCT international application(s) designating at least one country other than the United States of America filed by me on the same subject matter having a filing date before that of the application(s) of which priority is claimed:

PRIOR FOREIGN/PCT APPLICATION(S) AND ANY PRIORITY CLAIMS UNDER 35 U.S.C. 119:

COUNTRY	APPLICATION NUMBER	DATE OF FILING Iday, month, yearl	PRIORITY CLAIMED UNDER 35 USC 119	
Japan	11 204254		₩ YES	
Japan	11-204354	19.07.1999	☐ YES	□ №0
			□ YES	0 20
				□ ~0
			□ YES	□ ~0
		or organisms of country	C C C C C C C C C C C C C C C C C C C	